



Diesel Winter Care 1:1000



Reaction time
works during operation



Application field
all diesel engines



Consumption
150 ml for 150 l diesel // concentrate 1:1000



Application interval
on demand

Application Add regularly during the winter months before start of the frost periods to the tank before filling up. GAT Diesel Winter Care shall be used before gelling of the diesel fuel at approx. 0°C fuel temperature respectively during fill up the diesel tank. Application ratio 1:1000 (150 ml sufficient for 150 L diesel fuel). Product works during operation. Also suitable for stationary diesel engines.
Advice: Store under frost-free conditions! Shake well before use!

Description GAT Diesel Winter Care ensures improved flow properties of all diesel fuels and is suitable for use in all diesel aggregates with or without diesel particulate filter. Winter safe down to -28°C (depending on the fuel quality). Reliably prevents from formation of paraffin crystals at low temperatures.

Benefits Optimal flow properties of the diesel fuel ensure optimal operation of all system components and safe driving conditions. Easy application. Provides for a safe operation of diesel aggregates in winter periods. Maintains the flow properties of the fuel. Improves the filterability of the diesel fuel and prevents from blocking of the fuel filter. Ensures improved cold start properties in the winter period.

PU 24 x 150 ml // 12 x 1000 ml

Packing sizes 150 ml // Art.nr. 62008
1 L // Art.nr. 62070
5 L // Art.nr. 62071
10 L // Art.nr. 62025
30 L // Art.nr. 62026
// other sizes available on request

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.