



## Radiator Sealant



**Reaction time**  
approx. 10 minutes



**Application field**  
all cooling systems



**Consumption**  
300 ml for up to 12 l // resp. 25 ml for 1 l coolant



**Application interval**  
add with every filling

- Application**
- 1) Check the coolant level.
  - 2) Add the product to the warm cooling system. Move all heater controls to "hot".
  - 3) Let the engine idle for approx. 10 minutes.
  - 4) Check the coolant level again and test if the sealing was successful.
- Attention: Open radiator filling port slowly and successively - risk of burning!  
300 ml sufficient for cooling systems of 12 L capacity.  
For larger volumes add 25 ml per litre coolant.

**Description** GAT Radiator Sealant for use in all water-cooled, closed cooling systems (commercial vehicles, passenger cars, industrial heat exchangers). Reliably seals critical hairline cracks and small leaks - quick and easy. Also for preventive usage.

**Benefits** The major part of chemical energy that is bound in the fuel is converted into heat during the combustion process which must be dissipated. Therefore a fully functional cooling system is of major importance for the operational liability of engines! Helps to avoid expensive repair works. Prevents from loss of cooling liquid and protects against engine damage.

**PU** 24 x 300 ml

**Packing sizes** 300 ml // Art.nr. 62011  
5 L  
// other sizes available on request

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.