







## Air Intake Cleaner Diesel

-  **Reaction time**  
approx. 30 minutes
-  **Application field**  
all diesel engines
-  **Consumption**  
300 ml for 1 application
-  **Application interval**  
every 6 months /// on demand

**Application** GAT Air Intake Cleaner is exclusively developed for application with the „GAT Stream“ device and suitable adapters.  
Check the engine oil level before application. If the engine oil is contaminated with diesel fuel, an oil change has to be carried out before cleaning of the diesel particulate filter can be done.

- 1) spray approx. 150 ml evenly in all intake ducts by moving the adapter back and forth.
- 2) Let the product take effect for approx. 30 mins, then start the engine.
- 3) Let the engine run at 2500 rpm.
- 4) Spray the remaining product intermittently into air intake system.
- 5) Finally check the valve clearance.

**Description** For the cleaning of the entire air intake system. Removes deposits in the air intake system, combustion chamber, throttle valves, inlet and outlet valves and valve seats. Especially recommended for insufficient throttle response and compression as well as engine knocking and dieseling.

**Benefits** Only a clean fuel system guarantees clean and powerful combustion and efficient engine performance! Reduces the fuel consumption and the exhaust gas emission values. Ensures a smooth idling.

**PU** 24 x 300 ml

**Packing sizes** 300 ml // Art.nr. 62034  
// other sizes available on request

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.